



EBOX-333x Series, LAN x 1, RS-232 x 2, 4G LTE

Model Type	EB-3330-SIM	EB-3330-C2SIM	EB-3330-B1C2SIM	
	EB-3332-SIM	EB-3332-C2SIM	EB-3332-B1C2SIM	
Processor	DM&P Vortex86DX2 (933MHz)			
BIOS	AMI BIOS			
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series			
VGA	Integrated Graphics Chip/ D-Sub 15-pin			
Maximum Resolution	1920 x 1440 pixels			
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)			
USB 2.0	External: 3 ports (Front x 2, Rear x 1)			
HD Audio	Line out			
I/O	SD Slot	1x		
	SATA	1x (not support 2.5" SATA HDD)		
	mPCIe & SIM card slot	1x		
	COM1	N/A	RS-232	
	COM2		RS-232	
	COM3	N/A	N/A	
	COM4		CANbus	
Auto Power On	Yes			
Power	DC +8V~+24V			
Dimensions	115 x 115 x 35mm			
Unit Net Weight	510g			
Operation Temp.	5~50 °C			
Certifications	CE, FCC, VCCI			
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232			

Features:

- * DM&P Vortex86DX2 (933MHz)
- * Onboard 1GB/ 2GB DDR2
- * SD, SDHC support
- * VESA mounting support
- * Fanless design
- * 4G LTE support
- * 10/100 Mbps LAN x 1
- * PXE Diskless Boot
- * USB 2.0 port x 3
- * RS-232 port x 2
- * CANbus port x 1
- * Auto Power On support
- * Ultra low power