



## EBOX-336x Series, LAN x 2, RS-485 x3, x4, SD, SATA

Model Type	EB-3360-L2853	EB-3360-L2854	EB-3360-L2C2852E	EB-3360-L2C2851G1E	
	EB-3362-L2853	EB-3362-L2854	EB-3362-L2C2852E	EB-3362-L2C2851G1E	
Processor	DM&P Vortex86DX3 (1GHz)				
BIOS	AMI BIOS				
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin				
Maximum Resolution	1920 x 1080 pixels				
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio	Mic in and Line out				
I/O	SD Slot	1x	N/A	N/A	N/A
	SATA	1x			
	COM1	RS-485	RS-485	RS-232	RS-232
	COM2	RS-485	RS-485	RS-232	RS-232
	COM3	N/A	RS-485	RS-485	RS-485
	COM4	RS-485	RS-485	RS-485	8-bit GPIO
Auto Power On	Yes				
Power	DC +8V~+24V				
Dimensions	115 x 115 x 35mm				
Unit Net Weight	510g				
Operation Temp.	5~50 °C				
Certifications	CE, FCC, VCCI				
Optional	1. Internal SD Card slot 2. TTL Level RS-232 3. mPCIe				

### Features:

- \* DM&P Vortex86DX3 (1GHz)
- \* Onboard 1GB/ 2GB DDR3
- \* SATA DOM, 2.5" HDD, SSD support
- \* VESA mounting support
- \* Fanless design
- \* SD, SDHC support
- \* 4G LTE support
- \* 10/100 Mbps LAN x 1, 1 Gbps LAN x 1
- \* Wireless LAN Dongle support (Optional)
- \* PXE Diskless Boot
- \* USB 2.0 port x 4
- \* RS-485 Up to 4 ports
- \* RS-232 Up to 4 ports
- \* 8-bit GPIO Up to 4 ports
- \* Auto Power On support
- \* Ultra low power