



EBOX-336x Series, LAN x 1, RS-232 x 2, RS-485 x 1, 4G LTE, CANbus

Model Type	EB-3360-SIM	EB-3360-C2SIM	EB-3360-C2G2SIM	EB-3360-B1C2SIM	EB-3360-B1853SIM	EB-3360-851SIM	EB-3360-852SIM	
	EB-3362-SIM	EB-3362-C2SIM	EB-3362-C2G2SIM	EB-3362-B1C2SIM	EB-3362-B1853SIM	EB-3362-851SIM	EB-3362-852SIM	
Processor	DM&P Vortex86DX3 (1GHz)							
BIOS	AMI BIOS							
Memory	Onboard 1GB DDR3 for 3360 Series/ Onboard 2GB DDR3 for 3362 Series							
VGA	Integrated Graphics Chip/ D-Sub 15-pin							
Maximum Resolution	1920 x 1440 pixels							
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)							
USB 2.0	External: 3 ports (Front x 2, Rear x 1)							
HD Audio	Line out							
I/O	SD Slot	1x						
	SATA	1x (not support 2.5" SATA HDD)						
	mPCIe & SIM card slot	1x						
	COM1	N/A	RS-232	8-bit GPIO	RS-232	RS-485	RS-485	RS-485
	COM2		RS-232	8-bit GPIO	RS-232	RS-485	N/A	RS-485
	COM3		N/A	RS-232	N/A	RS-485		N/A
	COM4			RS-232	CANbus	CANbus		
Auto Power On	Yes							
Power	DC +8V~+24V							
Dimensions	115 x 115 x 35mm							
Unit Net Weight	510g							
Operation Temp.	5~50 °C							
Certifications	CE, FCC, VCCI							
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232							

Features:

- * DM&P Vortex86DX3 (1GHz)
- * Onboard 1GB/ 2GB DDR3
- * SATA DOM support
- * SD, SDHC support
- * VESA mounting support
- * Fanless design
- * 4G LTE support
- * 10/100 Mbps LAN x 1
- * PXE Diskless Boot
- * USB 2.0 port x 3
- * RS-232 Up to 2 ports
- * RS-485 Up to 3 ports
- * 8-bit GPIO port x 2
- * CANbus port x 1
- * Auto Power On support
- * Ultra low power